



Installation instructions for IGNITION COIL

(Lighting coil can be added)

HONDA CR500 1987-ON

- ❖ Take the ignition cover off.
- ❖ Take note of the wire colors of the original stator wires and disconnect them from the wiring loom.
- ❖ Remove the flywheel using a proper puller tool.
- ❖ Remove the baseplate with the original stator.
- ❖ Remove the screws that secure the coil and take the coil off.
- ❖ Cut the original wires from the stator close to the original coil. Take a good look how the wires are connected to the coil. (at which side of the original coil which wire color goes).
- ❖ Connections: Connect the BLUE and WHITE wires according to the drawing
- ❖ Connect the old wires up to the new coil. Put the wires in exactly the same place as on the original. Make sure you have good connections here. Use a soldering iron and rosin core solder (the type used in electrical applications).
- ❖ Mount the coil onto the baseplate, fit the screws using locking compound on the threads and **TIGHTEN THE SCREWS SECURELY!**
- ❖ Refit the stator baseplate. Ensure the wires **CANNOT TOUCH THE FLYWHEEL!** (especially on the inside of the flywheel).
- ❖ Refit the flywheel. Tighten the bolt to specified torque.
- ❖ Fit the ignition cover.
- ❖ If you experience any problems, contact us at:

Ricky Stator

1672 Main St., Ste. E, PMB 104, Ramona CA 92065
(760) 787-0094 • Fax 787-0313
E-mail: stator@adnc.com • www.rickystator.com